

DESCRIPTION

- The Aquastyle displays air and water temperature and local time and date.
- Radio communication between temperature probes and the Aquastyle.
- High luminosity red LED display adapted to indoor or outdoor environment.
- In addition to time and temperatures, it can display humidity (with wired probe) and chlorine (manually).
- Aquastyle can be used as a timer/stopwatch with its supplied HF remote control.



NORMS

- RADIO Standard: EN 300-220,
- CEM Standard for RADIO products: EN 301-489,
- Safety Standard: NF EN60950.



GENERAL FEATURES

- **Temperature display unit**..... ° or 1/10° Celsius.
- **Upper line display**..... 4 digits, 15cm, time, date, air T° or humidity.
- **2nd and 3rd line display**..... 2 x 4 digits, 10cm, temperatures, humidity and chlorine.
- **Digits**..... Red SMD LED 120°.
- **Communication with pool temperature probes**..... HF 869 Mhz.
- **Receiver**..... Integrated DHF temperature and time receiver.
- **Temperature probes offset adjustment**.. -9.9° to 9.9 °.
- **Menu and parameter setting**..... HF 4-button remote control.
- **Installation**..... Indoor pool area or outdoor.
- **Operation**..... Silent.
- **Optional**..... - 1 wired air temperature and humidity input,
- Radio synchronisation by Nanotime time base.



MECHANICAL FEATURES

- **Electrical insulation**..... Class 1.
- **Construction**..... Aluminium casing, IP54, IK07.
- **Operating temperature range**..... -20° to 50°C.
- **Humidity**..... 93% at 40°C.
- **Weight**..... 13,5 Kg.



Dimensions in mm

ELECTRICAL FEATURES

- **Power source**..... 100 - 240V ±10% 50/60Hz (2.5 m power cord included).
- **Consumption**..... 100 - 240 VAC ; 2 - 1,2 A.

REFERENCES

- **935 831**..... Aquastyle LED display (pool area)
- **935 835**..... Wireless pool temperature probes (supplied with 2 T° probes and 2 thermowells)
- **935 836**..... Polycarbonate front glass with 2 adhesive texts
- **939 041**..... Wireless Air Temperature probe (battery powered) - option
- **939 045**..... Wired Air Temperature/Humidity probe (5m cable) - option
- **927 272**..... NANOTIME DCF – DHF 230V
- **927 273**..... NANOTIME GPS – DHF 110 to 230V



Wired Air T° / Humidity probe

Wireless Air T° probe

